
APPENDIX E

**WASATCH FRONT URBAN AREA
LONG RANGE TRANSPORTATION PLAN UPDATE**

2004-2030

**WASATCH FRONT URBAN AREA
LONG RANGE TRANSPORTATION PLAN UPDATE
2004-2030
FUNCTIONAL CLASSIFICATION DEFINITIONS**

Streets and highways in this Long Range Transportation Plan are classified according to the following definitions:

Principal Arterial Street System: The urban principal arterial street system should serve the projected major centers of activity of a metropolitan area, the highest projected traffic volume corridors, and the longest projected trips. It should also carry a high proportion of the total projected urban area travel on a minimum of mileage. The principal arterial system should carry the major portion of forecasted trips entering and leaving the urban area, as well as the majority of through movements desiring to bypass the central city. In addition, forecasts of significant intra-area travel, such as between major inner-city communities, or between major suburban centers should be served by principal arterials. Finally, this system in urbanized areas should connect with all the major rural arterials which enter the urban area.

Minor Arterial Street System: The minor arterial street system should interconnect with and augment the urban principal arterial system and provide service to forecasted trips of moderate length at a somewhat lower level of travel mobility than principal arterials. This system also distributes travel to geographic areas smaller than those identified with the higher system. The minor arterial street system includes all arterials not classified as principal and contains facilities that place more emphasis on land access than the higher system, and offer a lower level of traffic mobility. Such facilities may be expected to provide for movement within communities, but ideally should not penetrate identifiable neighborhoods.

Collector Street System: The collector street system differs from the arterial systems in that facilities on the collector system may penetrate neighborhoods distributing trips from the arterials through the area to the ultimate destination, which may be located on a local or collector street. Conversely, the collector street can also be expected to collect traffic from local streets in the neighborhood and channel it into the arterial systems. In the development of the functional plan, use of the collector system by through traffic should be discouraged. The collector system should provide for both land access service and local traffic movements with residential neighborhoods, commercial areas, or industrial areas.

Local Street System: The local street system comprises all facilities not on one of the higher systems. It serves primarily to provide direct access to abutting land and access to the higher order systems. It offers the lowest level of mobility. Service to through traffic movements should be deliberately discouraged.

